


WALL WASHER



High quality wall washer illumination
Hohe Wallwasher Beleuchtungsqualität



NEKO/ FW
FUSION WALL WASHER

NEKO/ FW
FUSION WALL WASHER



FW5-11W 600 Lm WHITE MODELS (White housing, Black Reflector, CREE LED)

Code	BEAM	CCT	CRI	LED output	Downlight output	LED Power	Current	Voltage
A751131(X)	24°	3000K	83	1300 lm	600 lm	11 W	700 mA	16V
A751132(X)	24°	4000K	83	1400 lm	650 lm	11 W	700 mA	16V
A751137(X)	40°	3000K	90	1200 lm	550 lm	11 W	700 mA	16V
A751138(X)	40°	4000K	90	1300 lm	600 lm	11 W	700 mA	16V

FW5-11W 600 Lm BLACK MODELS (Black housing, Black Reflector, CREE LED)

Code	BEAM	CCT	CRI	LED output	Downlight output	LED Power	Current	Voltage
A753131(X)	24°	3000K	83	1300 lm	600 lm	11 W	700 mA	16V
A753132(X)	24°	4000K	83	1400 lm	650 lm	11 W	700 mA	16V
A753137(X)	40°	3000K	90	1200 lm	550 lm	11 W	700 mA	16V
A753138(X)	40°	4000K	90	1300 lm	600 lm	11 W	700 mA	16V

FW75-11W 600 Lm WHITE MODELS (White housing, Black Reflector, CREE LED)

Code	BEAM	CCT	CRI	LED output	Downlight output	LED Power	Current	Voltage
B751131(X)	24°	3000K	83	1300 lm	600 lm	11 W	700 mA	16V
B751132(X)	24°	4000K	83	1400 lm	650 lm	11 W	700 mA	16V
B751137(X)	40°	3000K	90	1300 lm	550 lm	11 W	700 mA	16V
B751138(X)	40°	4000K	90	1400 lm	600 lm	11 W	700 mA	16V

FW75-11W 600 Lm BLACK MODELS (Black housing, Black Reflector, CREE LED)

Code	BEAM	CCT	CRI	LED output	Downlight output	LED Power	Current	Voltage
B753131(X)	24°	3000K	83	1300 lm	600 lm	11 W	700 mA	16V
B753132(X)	24°	4000K	83	1400 lm	650 lm	11 W	700 mA	16V
B753137(X)	40°	3000K	90	1300 lm	550 lm	11 W	700 mA	16V
B753138(X)	40°	4000K	90	1400 lm	600 lm	11 W	700 mA	16V

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

FW10-22W 1200 Lm WHITE MODELS (White housing, Black Reflector, CREE LED)

Code	BEAM	CCT	CRI	LED output	Downlight output	LED Power	Current	Voltage
A701131(X)	24°	3000K	83	2600 lm	1200 lm	22 W	700 mA	31V
A701132(X)	24°	4000K	83	2850 lm	1300 lm	22 W	700 mA	31V
A701137(X)	40°	3000K	90	2300 lm	1100 lm	22 W	700 mA	31V
A701138(X)	40°	4000K	90	2500 lm	1200 lm	22 W	700 mA	31V

FW10-22W 1200 Lm BLACK MODELS (Black housing, CREE LED, Black Reflector)

Code	BEAM	CCT	CRI	LED output	Downlight output	LED Power	Current	Voltage
A703131(X)	24°	3000K	83	2600 lm	1200 lm	22 W	700 mA	31V
A703132(X)	24°	4000K	83	2850 lm	1300 lm	22 W	700 mA	31V
A703137(X)	40°	3000K	90	2300 lm	1100 lm	22 W	700 mA	31V
A703138(X)	40°	4000K	90	2500 lm	1200 lm	22 W	700 mA	31V

FWT10-22W 1200 Lm WHITE MODELS (White housing, Black Reflector, CREE LED)

Code	BEAM	CCT	CRI	LED output	Downlight output	LED Power	Current	Voltage
B701131(X)	24°	3000K	83	2600 lm	1200 lm	22 W	700 mA	31V
B701132(X)	24°	4000K	83	2850 lm	1300 lm	22 W	700 mA	31V
B701137(X)	40°	3000K	90	2300 lm	1100 lm	22 W	700 mA	31V
B701138(X)	40°	4000K	90	2500 lm	1200 lm	22 W	700 mA	31V


FWT10-22W 1200 Lm BLACK MODELS (Black housing, Black Reflector, CREE LED)

Code	BEAM	CCT	CRI	LED output	Downlight output	LED Power	Current	Voltage
B703131(X)	24°	3000K	83	2600 lm	1200 lm	22 W	700 mA	31V
B703132(X)	24°	4000K	83	2850 lm	1300 lm	22 W	700 mA	31V
B703137(X)	40°	3000K	90	2300 lm	1100 lm	22 W	700 mA	31V
B703138(X)	40°	4000K	90	2500 lm	1200 lm	22 W	700 mA	31V

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

Below are light distribution diagrams for the Fusion wall washer 5 LED in 3000K.

Nachfolgend sind die Lichtverteilungsdiagramme für den Fusion wall washer 5 LED mit 3000K



Below are light distribution diagrams for the Fusion wall washer 10LED in 3000K.

Nachfolgend sind die Lichtverteilungsdiagramme für den Fusion wall washer 10LED mit 3000K

