


NIGEA LED

Park and Street Luminaires



Description: Ground-mounted LED bollard
 Light distribution: direct
 Optical system: matt aluminium reflector, clear polycarbonate diffuser, impact resistant
 Housing: aluminium
 Colour: dark grey (RAL7043)

General data: Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 50000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP54
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

Installation: On the ground (flange mounting plate included). Screw terminal, 3x1x1.5mm²

Environment: Outdoor

Application: Park, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Nigea LED1x1650 E800 T830	165	165	800	1542	14,3	108	80+	3000	3,50
Nigea LED1x1650 E800 T840	165	165	800	1627	14,3	113	80+	4000	3,50

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

DALI	Driver with DALI interface and switch-control dimming	T830	Colour temperature 3000K, CRI 80+
RAL	RAL colour	T840	Colour temperature 4000K, CRI 80+

STANDARD

