


# STAR LED

## Park and Street Luminaires



**Images for the product family and options:**



**Description:** Pole-mounted low-cost LED street luminaire  
 Light distribution type: direct  
 Optical system: frosted polycarbonate diffuser, UV stabilized, impact resistant  
 Housing: aluminium  
 Colour: dark grey (RAL 7043)

**General data:** Mains voltage: 220-240V, 50/60Hz  
 LED lifetime, h: 35000/L70B50  
 SDCM: 6  
 Protection class IEC: I  
 Ingress protection code: IP65  
 Mechanical impact resistance: IK08  
 Operating temperature range, °C: ta -20...+40

**Installation:** With two screws on Ø60mm horizontal pole, on the wall (mounting bracket to be ordered separately). Cable, 0.3m, 3x1.00mm<sup>2</sup>

**Environment:** Outdoor

**Application:** Parking area, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Star LED1x5000 E918 T740	396	170	88	5000	50	100	70+	4000	1,25

\* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

**Available options:**  
 T740 Colour temperature 4000K, CRI 70+

**Available accessories:**



Product: WALL MTG bracket (Street LED D60mm 10° P7035S)  
 Description: Bracket for street luminaire installation onto wall, pole diameter D60mm, 10° angle, l. grey, 1pcs

**STANDARD**

