



BOOTES Q LED

Surface and Suspended Luminaires



Images for the product family and options:



Description:

Surface decorative LED luminaire
 Light distribution type: direct/indirect
 Optical system: opal PMMA diffuser/ matt micro-prismatic PMMA diffuser, UGR≤19
 Housing: steel
 Colour: grey (RAL9006), white (9003), black (RAL9005)

General data:

Mains voltage: 220-240V, 0/50/60Hz
 LED lifetime, h: 100000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP20
 Mechanical impact resistance: IK02
 Operating temperature range, °C: ta 0...+35

Installation:

On the ceiling, on the wall, suspended (accessories to be ordered separately). Push-in terminal, 3x2x2.5mm2

Environment:

Indoor

Application:

Office, education, retail, public place



Bootes Q LED luminaire with suspension MTG KIT Bootes Q LED.
 For more information, please check the option and accessories lists.

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI *	CCT*, K	Weight, kg
Bootes Q LED1x2250 G568 T830 OP	300	300	90	2179	16,1	135	80+	3000	2,70
Bootes Q LED1x2500 G569 T830 OP	300	300	90	2485	17,6	141	80+	3000	2,70
Bootes Q LED1x2750 G570 T830 OP	300	300	90	2789	19,7	142	80+	3000	2,70
Bootes Q LED1x3850 G571 T830 OP	450	450	90	3742	25,8	145	80+	3000	5,14
Bootes Q LED1x4600 G572 T830 OP	450	450	90	4489	30,8	146	80+	3000	5,14
Bootes Q LED1x5350 G573 T830 OP	450	450	90	5230	35,8	146	80+	3000	5,14
Bootes Q LED1x5750 G574 T830 OP	600	600	90	5612	37,7	149	80+	3000	8,65
Bootes Q LED1x6900 G575 T830 OP	600	600	90	6736	45,5	148	80+	3000	8,65
Bootes Q LED1x8050 G576 T830 OP	600	600	90	7853	52,3	150	80+	3000	8,65
Bootes Q LED1x9150 G577 T830 OP	900	900	90	8932	59,1	151	80+	3000	17,41
Bootes Q LED1x10700 G578 T830 OP	900	900	90	10450	68,4	153	80+	3000	17,41
Bootes Q LED1x12250 G579 T830 OP	900	900	90	11962	79,3	151	80+	3000	17,41

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI *	CCT*, K	Weight, kg
Bootes Q LED1x2250 G568 T840 OP	300	300	90	2255	16,1	140	80+	4000	2,70
Bootes Q LED1x2500 G569 T840 OP	300	300	90	2531	17,6	144	80+	4000	2,70
Bootes Q LED1x2750 G570 T840 OP	300	300	90	2805	19,7	143	80+	4000	2,70
Bootes Q LED1x3850 G571 T840 OP	450	450	90	3918	25,8	152	80+	4000	5,14
Bootes Q LED1x4600 G572 T840 OP	450	450	90	4700	30,8	152	80+	4000	5,14
Bootes Q LED1x5350 G573 T840 OP	450	450	90	5475	35,8	153	80+	4000	5,14
Bootes Q LED1x5750 G574 T840 OP	600	600	90	5875	37,7	156	80+	4000	8,65
Bootes Q LED1x6900 G575 T840 OP	600	600	90	7053	45,5	155	80+	4000	8,65
Bootes Q LED1x8050 G576 T840 OP	600	600	90	8222	52,3	157	80+	4000	8,65
Bootes Q LED1x9150 G577 T840 OP	900	900	90	9352	59,1	158	80+	4000	17,41
Bootes Q LED1x10700 G578 T840 OP	900	900	90	10941	68,4	160	80+	4000	17,41
Bootes Q LED1x12250 G579 T840 OP	900	900	90	12524	79,3	158	80+	4000	17,41
Bootes Q LED1x2250 G568 T830 DPRZ LT80	300	300	90	1971	16,1	122	80+	3000	2,70
Bootes Q LED1x2500 G569 T830 DPRZ LT80	300	300	90	2249	17,6	128	80+	3000	2,70
Bootes Q LED1x2750 G570 T830 DPRZ LT80	300	300	90	2524	19,7	128	80+	3000	2,70
Bootes Q LED1x3850 G571 T830 DPRZ LT80	450	450	90	3386	25,8	131	80+	3000	5,14
Bootes Q LED1x4600 G572 T830 DPRZ LT80	450	450	90	4061	30,8	132	80+	3000	5,14
Bootes Q LED1x5350 G573 T830 DPRZ LT80	450	450	90	4732	35,8	132	80+	3000	5,14
Bootes Q LED1x5750 G574 T830 DPRZ LT80	600	600	90	5077	37,7	135	80+	3000	8,65
Bootes Q LED1x6900 G575 T830 DPRZ LT80	600	600	90	6095	45,5	134	80+	3000	8,65
Bootes Q LED1x8050 G576 T830 DPRZ LT80	600	600	90	7105	52,3	136	80+	3000	8,65
Bootes Q LED1x9150 G577 T830 DPRZ LT80	900	900	90	8082	59,1	137	80+	3000	17,41
Bootes Q LED1x10700 G578 T830 DPRZ LT80	900	900	90	9455	68,4	138	80+	3000	17,41
Bootes Q LED1x12250 G579 T830 DPRZ LT80	900	900	90	10823	79,3	136	80+	3000	17,41
Bootes Q LED1x2250 G568 T840 DPRZ LT80	300	300	90	2041	16,1	127	80+	4000	2,70
Bootes Q LED1x2500 G569 T840 DPRZ LT80	300	300	90	2290	17,6	130	80+	4000	2,70
Bootes Q LED1x2750 G570 T840 DPRZ LT80	300	300	90	2538	19,7	129	80+	4000	2,70
Bootes Q LED1x3850 G571 T840 DPRZ LT80	450	450	90	3545	25,8	137	80+	4000	5,14
Bootes Q LED1x4600 G572 T840 DPRZ LT80	450	450	90	4252	30,8	138	80+	4000	5,14
Bootes Q LED1x5350 G573 T840 DPRZ LT80	450	450	90	4954	35,8	138	80+	4000	5,14
Bootes Q LED1x5750 G574 T840 DPRZ LT80	600	600	90	5316	37,7	141	80+	4000	8,65
Bootes Q LED1x6900 G575 T840 DPRZ LT80	600	600	90	6381	45,5	140	80+	4000	8,65
Bootes Q LED1x8050 G576 T840 DPRZ LT80	600	600	90	7439	52,3	142	80+	4000	8,65
Bootes Q LED1x9150 G577 T840 DPRZ LT80	900	900	90	8461	59,1	143	80+	4000	17,41
Bootes Q LED1x10700 G578 T840 DPRZ LT80	900	900	90	9899	68,4	145	80+	4000	17,41
Bootes Q LED1x12250 G579 T840 DPRZ LT80	900	900	90	11331	79,3	143	80+	4000	17,41


* Tolerance range for optical and electrical data: $\pm 10\%$. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:


T830 Colour temperature 3000K, CRI 80+
 T840 Colour temperature 4000K, CRI 80+
 OP Opal diffuser with high light transmittance
 DPRZ LT80 De-glaring micro-prismatic diffuser with matt light scattering layer
 DALI Driver with DALI interface
 *note - minimum dimming level is 10%, exemption 1% for models (G568, G569, G570)
 EAIR-M Master luminaire with integrated smart sensor and driver with wireless communication and grouping possibilities for lighting control
 EAIR-S Slave luminaire with integrated EAIR type driver for lighting control
 *note - max system size 1x EAIR-M + 3x EAIR-S
 *note - max wire length from EAIR-M to last EAIR-S - 11 meter
 *note - EAIR option not applicable for models: (G568, G569, G570)
 BLT Integrated wireless control unit and driver for lighting control via mobile device (via Bluetooth)
 COR Driver with Corridor function (never off)

COR1min Driver with Corridor function 1min (switch off after 1 min.)
 COR30min Driver with Corridor function 30min (switch off after 30 min.)
 *note - COR options not applicable for models: (G568, G569, G570)
 MW Integrated microwave (MW) motion sensor with on-off control
 EM3 Emergency version 3 hours
 EM3B Emergency version 3 hours (best available technology)
 EM3A Emergency version equipped with an autonomous testing system, 3 hours
 EM3D Emergency version 3 hours with DALI interface
 *note - EM options not applicable for models: (G568, G569, G570)
 1G Strain relief for power supply cable
 CBF3-2.0m clear Cable 3x0.75mm² for suspended luminaire up to 2.0 meters, transparent
 CBF5-2.0m clear Cable 5x0.75mm² for suspended luminaire up to 2.0 meters, transparent
 RAL RAL colour

OP



DPRZ LT80



Available accessories:



Product: Suspension MTG KIT SUSI
Description: Suspension wire set "I" type, 1.5m adjustable, 1pcs
*note - 4pcs MTG SUSI KIT for Bootes Q LED



Product: CAP4, white
Description: Steel cap for hiding cable inlet into ceiling, white/ grey/ black



Product: CAP cable 3x0.75 2.0m clear
Description: Cable 3x0.75mm² for suspended luminaire up to 2.0 meters, transparent



Product: Suspension MTG KIT Bootes Q LED white/ grey/ black
Description: Suspension wire set with cap 4x"I" type, 1.5m adjustable, 1pcs