


# MONTBLANC LED

## High-bays



**Description:** Suspended low-bay LED luminaire  
Light distribution type: direct  
Optical system: frosted tempered glass diffuser  
Housing: aluminium  
Colour: silver

**General data:** Mains voltage: 220-240V, 50/60Hz  
LED lifetime, h: 50000/L80B50  
SDCM: 3  
Protection class IEC: I  
Ingress protection code: IP20  
Mechanical impact resistance: IK04  
Operating temperature range, °C: ta 0...+40

**Installation:** Suspended (decorative chain, cap and cable included). Push-in terminal, 3x2x2.5mm2

**Environment:** Indoor

**Application:** Retail, showroom, hall, exhibition, public place



A lighting fixture is supplied with suspension chain, decorative cap and out-going cable for easy installation

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Montblanc LED1x2550 D016 T830	330	330	350	2443	27,1	90	80+	3000	4,60
Montblanc LED1x3650 D017 T830	330	330	350	3518	41,4	85	80+	3000	4,60
Montblanc LED1x4700 D018 T830	330	330	350	4512	57,2	79	80+	3000	4,60
Montblanc LED1x2550 D016 T840	330	330	350	2519	27,1	93	80+	4000	4,60
Montblanc LED1x3650 D017 T840	330	330	350	3626	41,4	88	80+	4000	4,60
Montblanc LED1x4700 D018 T840	330	330	350	4651	57,2	81	80+	4000	4,60

\* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

**Available options:**

- DALI Driver with DALI interface
- RAL RAL colour
- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+

**STANDARD**

