


PRIZMA LED

High-bays



Images for the product family and options:



Description: Suspended low-bay LED luminaire
Light distribution type: direct
Optical system: prismatic polycarbonate reflector
Housing: aluminium
Colour: dark grey (RAL 7043)

General data: Mains voltage: 220-240V, 50/60Hz
LED lifetime, h: 50000/L80B50
SDCM: 3
Protection class IEC: I
Ingress protection code: IP23
Mechanical impact resistance: IK02
Operating temperature range, °C: ta 0...+40°C

Installation: Suspended (hook for wire suspension included). Screw terminal, 3x1x2.5mm²

Environment: Indoor

Application: Retail, showroom, hall, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Prizma LED1x4150 D434 T830	410	410	425	3958	32,8	121	80+	3000	3,50
Prizma LED1x5950 D435 T830	410	410	425	5833	51,3	114	80+	3000	3,50
Prizma LED1x9000 D436 T830	510	510	540	8825	80,1	110	80+	3000	5,80
Prizma LED1x11150 D437 T830	510	510	540	10825	98,3	110	80+	3000	5,80
Prizma LED1x4150 D434 T840	410	410	425	4112	32,8	125	80+	4000	3,50
Prizma LED1x5950 D435 T840	410	410	425	5950	51,3	116	80+	4000	3,50
Prizma LED1x9000 D436 T840	510	510	540	8963	80,1	112	80+	4000	5,80
Prizma LED1x11150 D437 T840	510	510	540	11105	98,3	113	80+	4000	5,80

* Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- DALI Driver with DALI interface and switch-control dimming
- RAL RAL colour
- T830 Colour temperature 3000K, CRI 80+
- T840 Colour temperature 4000K, CRI 80+
- T850 Colour temperature 5000K, CRI 80+

