


GRUS S LED

Outdoor Accent Lighting



Images for the product family and options:



Description: Surface mounted accent LED luminaire
 Light distribution type: direct
 Optical system: lenses, tempered glass diffuser, impact resistant
 Housing: aluminium
 Colour: dark grey (RAL7043)

General data: Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 50000/L70B50
 SDCM: 5
 Protection class IEC: I
 Ingress protection code: IP65
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

Installation: On the horizontal or vertical surface. Cable, 0.3m, 3x0.75mm2

Environment: Outdoor

Application: Facade illumination, public space

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Grus S LED1x800 C313 T740 L30	120	120	90	802	7,8	103	70+	4000	0,90
Grus S LED1x1100 C314 T740 L30	120	120	90	1087	11,3	96	70+	4000	0,90

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

- L10 Optics with 10x10° beam angle T730 Colour temperature 3000K, CRI 70+
- L15 Optics with 15x15° beam angle T740 Colour temperature 4000K, CRI 70+
- L15x38 Optics with 15x38° beam angle
- L30 Optics with 30x30° beam angle (standard)
- L50 Optics with 50x50° beam angle

