


LEO LED

Outdoor Accent Lighting



Images for the product family and options:



Description: Surface mounted accent LED luminaire
 Light distribution type: direct/indirect
 Optical system: opal polycarbonate diffuser, UV stable, impact resistant
 Housing: aluminium
 Colour: dark grey (RAL7043)

General data: Mains voltage: 220-240V, 50/60Hz
 LED lifetime, h: 50000/L80B50
 SDCM: 3
 Protection class IEC: I
 Ingress protection code: IP54
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

Installation: On the walls or ceiling. Push-in terminal, 3x2x2.5mm²

Environment: Outdoor

Application: Facade illumination, parking area, public space


Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Leo 1E27 C402	265	265	90						1,60
Leo LED1x1200 D034 T830	265	265	90	1118	13,6	82	80+	3000	1,70
Leo LED1x1200 D034 T840	265	265	90	1173	13,6	86	80+	4000	1,70
Leo 1E27 C402 LOUVER	265	265	100						1,90
Leo LED1x1200 D034 T830 LOUVER	265	265	100	688	13,6	50	80+	3000	2,00
Leo LED1x1200 D034 T840 LOUVER	265	265	100	722	13,6	53	80+	4000	2,00

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

DALI	Driver with DALI interface and switch-control dimming	RAL	RAL colour
MW	MW sensor	T830	Colour temperature 3000K, CRI 80+
LOUVER	Decorative louver	T840	Colour temperature 4000K, CRI 80+

STANDARD



LOUVER

