


TUBE S LED

Outdoor Accent Lighting



Description: Surface mounted LED wall washer
Light distribution type: direct/indirect
Optical system: tempered glass diffuser, impact resistant
Housing: aluminium
Colour: dark grey (RAL7043)

General data: Mains voltage: 220-240V, 50-60Hz
Protection class IEC: I
Ingress protection code: IP54
Mechanical impact resistance: IK08
Operating temperature range, °C: ta -25...+40

Installation: On the wall. Screw terminal, 3x1x1.5mm2

Environment: Outdoor

Application: Facade illumination

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Tube S 2GU10 O13	90	90	300						1,40
Tube S 1GU10 O14 UP	90	90	158						1,30
Tube S 1GU10 O15 DOWN	90	90	158						1,30
Tube S LED2x400 G865 T830 L40	90	90	300	760	8,4	90	80+	3000	1,50
Tube S UP LED1x400 G866 T830 L40	90	90	158	363	4,2	86	80+	3000	1,40
Tube S LED2x400 G865 T840 L40	90	90	300	794	8,4	95	80+	4000	1,50
Tube S UP LED1x400 G866 T840 L40	90	90	158	397	4,2	95	80+	4000	1,40

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

UP	With up light source only	RAL	RAL colour
DOWN	With down light source only	T830	Colour temperature 3000K, CRI 80+
L40	LED bulb with 40° beam angle	T840	Colour temperature 4000K, CRI 80+

2x L40

